

SUPER SLICK® BARRIER WAX & SPEED COATING



EDGEWATER INDUSTRIES 18570 TRIMBLE COURT SPRING LAKE, MI 49456 U.S.A. TOLL-FREE: 1.877.609.3343 PH: 616.846.7939 FX: 616.846.1473 WWW.EDGEWATERINDUSTRIES.COM



OVERVIEW

Super Slick® provides an easy-release wax barrier between the boat bottom and biofouling marine growth. Designed for boats that remain in water, Super Slick® not only keeps your boat cleaner, but it also makes end-of-season cleanup easier.

FEATURES & BENEFITS

- Eliminate sanding and bottom painting: Use Super Slick® as an economic alternative to the painstaking process of sanding and bottom painting.
- Full Surface Compatibility: Protects steel, aluminum, fiberglass, wood, rubber, and other surfaces that remain underwater. Great for outdrives, trim tabs, transducers, propellers, and even over old anti-fouling paint.
- Use in freshwater and saltwater alike. Results will vary depending on local water conditions and biofouling variance.
- Super Slick® wears like a bar of soap as the boat moves through the water. This abrasive action sheds off stubborn growth that was able to attach to the boat bottom while docked or anchored.
- Easy to apply, Super Slick® can be spread evenly over the surface using a sponge or damp cloth. It can be applied dry dock or underwater.
- Provides protection for up to 6 months. Durability and effectiveness may vary depending on local water conditions and boat usage.
- Super Slick® may also be used as a speed coating to reduce drag and improve boat performance.
- Superior value - It costs less than \$20 to treat the bottom of a 20-foot boat.

APPLICATIONS

- Super Slick® is perfect for protecting boats that remain in water for long periods of time. The wax barrier is not designed to harden or cure, so trailering will strip the wax off in spots. Furthermore, if Super Slick® is out of water for more than 12 hours, the wax will harden and effectiveness will diminish.
- Super Slick® is also ideal for boaters that are looking for an alternative to expensive anti-fouling bottom paints that contain metals or chemicals designed to kill marine growth. Super Slick® is not an anti-fouling product, but rather a barrier wax.



Super Slick® was used in the Bermuda Challenge Cup as a speed coating on the boat Red White & Two

HELPFUL TIPS

- It is very important to remember that Super Slick® is designed for surfaces that remain underwater. If applied to areas above the waterline, it can be difficult to remove at the end of the season.
- Some marine growth may be able to attach to the boat bottom even though Super Slick® has been applied. However, end-of-season cleanup is still much simpler because this growth is easily removed from the barrier coating.

AM1001

16 Fl.oz., UPC#:652455120019, 12/Cs,
Ea Wt: 1 lb., Cs Wt: 13 lbs.