

Super Slick Protective Boat Wax

MATERIAL SAFETY DATA SHEET

Manufactured by:

Edgewater Industries
18570 Trimble Ct
Spring Lake, MI 49456

SECTION I

TRADE NAME: Super Slick Protective Boat Coating
CODE NUMBER: AM1001
CHEMICAL NAME: Hydrocarbon Mixture
CHEMICAL FAMILY: Hydrocarbon
SYNONYMS: None
FORMULA: Proprietary
MOLECULAR WEIGHT: N/A

SECTION II - INGREDIENTS

Component	CAS No.	%
P) Super Slick Speed Coating		
1) Aliphatic Hydrocarbon	64741-65-7	< 50%
2) Proprietary Wax Compound		> 50%

SECTION 2-A OCCUPATIONAL EXPOSURE LIMITS

OSHA No. PEL/TWA	OSHA PEL/CEILING	OSHA PEL/STEL	ACGIH TLV/TWA	ACGIH TLV/STEL
1) 100ppm	-	-	-	-
2) 5mg/M3	-	-	-	-

[NOTE: if product is unlisted it indicates "No Data" in all categories listed in this sub-section. If an area is blank it indicates "NO DATA" for that category.]

*This value is for the fumes generated when heated

SARA TITLE III INFORMATION

NO.	EHS RQ(LBS) (*1)	EHS TPQ(LBS) (*2)	SEC313 (*3)	313 Cat (*4)	313/312 Cat (*5)
P				H1 P3	
1				H1 P3	

FOOTNOTES

*1 = Reportable quantity of extremely hazardous substance, section 302

*2 = Threshold planning quantity, extremely hazardous substance, section 302

*3 = toxic chemical, section 313

*4 = category as required by sec 313 (40 CFR 372.65 C), must use on toxic release inventory form.

*5 = Hazard category for SARA sec. 311/312 reporting

Super Slick Protective Boat Wax

Health:

H1 = immediate (acute) health hazard

H2 = delayed (chronic) health hazard

Physical:

P3 = Fire hazard

P4 = Sudden release of pressure hazard

P5 = Reactive hazard

SECTION III - PHYSICAL DATA

MELTING POINT @ 760 mm Hg:	145F
VAPOR PRESSURE mm Hg @20 C:	<1 mm Hg
SPECIFIC GRAVITY:	.83
SOLUBILITY IN WATER:	< 0.1%
pH:	Essentially Neutral
VISCOSITY:	Solid
VAPOR DENSITY:	>1 (Air = 1)
PERCENT VOLATILE BY VOLUME:	approx. 30% @1atm and 25C
POUR POINT:	approx. 150F
COLOR:	Tan-brown
APPEARANCE:	Solid paste
ODOR:	slight spirits odor
INTENSITY:	slight

SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT (T.C.C.):	>200F
AUTOIGNITION TEMPERATURE:	Unknown
FLAMMABILITY LIMITS IN AIR (% BY VOLUME): (Estimated values)	LOWER: 1.0% UPPER: 6.0%

GENERAL HAZARD: Combustible Solid

EXTINGUISHING MEDIA: Use water fog, foam, CO2 or dry chemical extinguishing media.

SPECIAL FIREFIGHTING PROCEDURES: Water may prove to be somewhat ineffective due to the solvents contained in this material. It should also be used to cool and protect exposed material and firefighters. Firefighters should be equipped with self-contained breathing apparatus and turnout gear.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known

EMERGENCY TELEPHONE NUMBER

CHEMTREC 1-800-424-9300 1-(201)-316-3000
This number is available days, nights, weekends, and holidays.

SECTION V - HEALTH DATA

TOXICOLOGICAL TEST DATA:	RESULT:
Rat, Oral LD50	No Data
Rabbit, Dermal LD50	No Data
Rabbit, Eye Irritation	NI, estimated moderate
Rabbit, Skin Irritation	NI, mildly irritating

Super Slick Protective Boat Wax

EFFECTS OF OVEREXPOSURE:

Health studies have shown that many hydrocarbons and lubricants pose potential human health risks that may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized. Product has a low order of acute oral and dermal toxicity, but small amounts aspirated into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death. Pre-existing medical conditions of dermatitis may be aggravated by this product.

FIRST AID PROCEDURES:

EYE CONTACT: Flush with clear water for 15 minutes or until irritation subsides. Seek medical attention.

SKIN CONTACT: Remove any contaminated clothing and wash skin thoroughly with soap and water immediately.

INHALATION: If overcome by vapor, remove from exposure and call a physician immediately. If breathing is irregular or has stopped, start resuscitation; qualified personnel should administer oxygen, if available.

INGESTION: DO NOT INDUCE VOMITING! Place victim on left side with the head down. Do not leave unattended. Call a physician immediately.

SECTION VII - SPECIAL PRECAUTIONS

RESPIRATORY PROTECTION: If vapors or mists are generated, wear a NIOSH/MSHA approved organic vapor/mist respirator.

EYE PROTECTION: Chemical goggles; also wear a face shield if splashing hazard exists.

PROTECTIVE CLOTHING: Gloves, coveralls, apron, boots as necessary to prevent skin contact.

VENTILATION: Use local exhaust to control vapors/mists.

OTHER: Keep containers closed when not in use. Do not store near heat. Static electricity may accumulate and create a fire hazard. Ground fixed equipment. Bond and ground transfer containers and equipment.

Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers.

SECTION VIII - ENVIRONMENTAL DATA

ENVIRONMENTAL TOXICITY DATA:

None Available

SPILL AND LEAK PROCEDURES:

Not applicable

CAUTION. COMBUSTIBLE. If a large spills of molten material occurs, eliminate potential sources of ignition. Wear appropriate respirator and other protective clothing. Shut off source of leak only if safe to do so. Dike and contain. Wait for material to cool and harden. Place in non-leaking containers and seal tightly for proper disposal. Flush area with sand to remove trace residue; dispose of flush powder as above.

WASTE DISPOSAL METHOD:

Incinerate in accordance with all local, state and federal regulations.

CONTAINER DISPOSAL METHOD: Dispose of with licensed facility. Recommend crushing or other means to prevent unauthorized reuse.

Super Slick Protective Boat Wax

SECTION IX - SHIPPING DATA

D.O.T. Proper Shipping Name (49CFR172.101-102)

Solid Boat Wax

D.O.T. Classification: Non-regulated
D.O.T. Identification Number: None
Name: Wax, Solid

D.O.T. Hazard Classification (CFR172.101-102)
PRIMARY: Combustible SECONDARY: none
D.O.T. Labels Required: None
D.O.T. Placards Required: None
Poison Constituent: None
BILL OF LADING DESCRIPTION: Solid Wax
CC No.: NI
UN/NA CODE: NA

INTERNATIONAL SHIPPING CLASS: Non-regulated

Label Required: None
Shipping Name: Solid Boat Wax

SECTION X - REGULATORY DATA

RCRA Status:

Under EPA-RCRA (40 CFR 261.21), If this product becomes a waste material, in certain applications it may be an ignitable hazardous waste. Hazardous Waste Number D001. Refer to latest EPA or STATE regulations regarding proper disposal.

CERCLA Status: NI

STATE RIGHT TO KNOW INFORMATION

None of the products contained in this liquid are listed on any state right-to-know legislation according to our information. Check your state regulations to determine any listing possibilities.

Updated: 4/30/2010

While Wilbur Products, Inc. and Edgewater Industries believe the data set forth herein are accurate and fulfill all current requirements as of the date hereof, Wilbur Products, Inc. makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation and verification.